

4. Specific Signs

4.1 Direction Signs

4.1.1 A direction sign shall not exceed 150mm in depth and 750mm in length.

4.2 Illuminated Sign

4.2.1 An illuminated sign:

- (a) and any boxing or casing enclosing it shall be constructed entirely of non-flammable material with the exception of the insulation of electric wires;
- (b) shall be so protected that if any glass, other than the glass of fluorescent tubing, breaks none of the glass can fall on any street, way, footpath or other public place.

4.2.2 The electrical installation of an illuminated sign shall be constructed and maintained in accordance with the requirements of and to the satisfaction of the State Energy Commission.

4.2.3 The light from an illuminated sign shall not be so intense as to cause annoyance to the public.

4.3 Verandah Sign

4.3.1 A sign above the outer fascia of a verandah shall be comprised only of free standing letters which are parallel to the nearest street kerb and each of which has a height of not more than 400mm. Each letter shall be mounted on a base of 75mm in height.

4.3.2 Subject to Sub-by-law 4.13, a sign fixed to the outer or return fascia of a verandah:

- (a) shall not exceed 600mm in height;
- (b) shall not project beyond the outer metal frame or other surround of the fascia;
- (c) in the case of an illuminated sign, shall not be a flashing sign. For the purpose of this paragraph an illuminated sign which only changes colour is not a flashing sign;
- (d) shall be so constructed that the bottom edge of the sign is not lower than the bottom edge of the fascia.

4.4 Sign Under Verandah

4.4.1 A sign fixed to the underside of a verandah:

- (a) shall not exceed 2400mm in length, 0.9m² in area and 600mm in height.
- (b) shall not weigh more than 60kg.
- (c) shall be fixed at right angles to the wall of the building in front of which the sign is erected provided that where such a sign is erected at a street intersection that sign may be placed at an angle to the wall so as to be visible from both streets.

4.4.2 If a sign fixed to the underside of a verandah exceeds 300mm in heights that sign shall not:

- (a) be located within 1350mm of the nearest side wall of the building; and
- (b) be located within 2700mm of another sign fixed to the underside of the verandah.

4.4.3 If a sign fixed to the underside of a verandah does not exceed 300mm in height that sign shall not:

- (a) be located within 900mm of the nearest side wall;
- (b) be located within 1800mm of another sign fixed to the underside of the verandah.

4.4.4 For the purpose of paragraph 4.4.2 and 4.4.3, the distance of a sign from a side wall shall be measured along the front of the building from the edge of the sign closest to that side wall.

4.5 Horizontal Sign

4.5.1 A horizontal sign:

- (a) shall be fixed parallel to the wall of the building to which it is attached;
- (b) shall not project more than 600mm from the wall to which it is attached;
- (c) shall not be within 600mm of either end of the wall to which it is attached unless the end of the sign abuts against a brick, stone or cement corbel pier or plaster which is at least

